MP52 Datasheet

Microsoft Phone MP52

A cost-effective basic Teams phone with high performance, the Android 12.0 OS-based Yealink MP52 is plentiful in practical functions and outstanding in calling experience. The design of a non-touchscreen with physical navigation buttons makes the phone suitable for the common area and the best migration practice from Skype for business to Teams. Powered by Microsoft, MP52 delivers a consistent Teams calling and meeting experience and improves productivity in daily work.



Key Features and Benefits

Excellent Calling Experience

The Yealink MP52 leverages the advantage of Yealink Optima HD voice and Noise Proof Technology. The full-duplex hands-free speakerphone with AEC & HAC handset makes the phone a high performance with crystal-clear sounds, and also keeps the process of each calling stably and smoothly.

Common Area Phone

That adopt to using in the common area, such as school/hospital/business scenarios, the Yealink MP52 is invulnerable to damage caused by the design of non-touchscreen and physical buttons. Moreover, the appearance of a reasonable panel structure and fewer buttons would be appropriate for deploying the phone in the common area. Users can connect Wi-Fi/Bluetooth dongle and compatible USB headset through the USB type-A port.

Efficient Management

Effectively, MP52 offers an auto-provisioning mechanism with phone development and configuration. Managers can also deploy, manage, and update the MP52 phone in various flexible ways, including Microsoft TAC, Yealink, and Unify Square device management platforms.

• Android 12.0

• 2.4 inch (320 x 240) Non-touch Color Screen

Yealink

- Optimal HD audio, Yealink Noise Proof Technology
- Magnet Handset
- Bluetooth Headset via Dongle BT41
- Wi-Fi via Dongle WF50
- USB Type-A port, Supports USB Headset
- Microsoft Teams-tailored APP
- Dual-port 10/100M Ethernet Switch, Supports PoE
- Supports Microsoft/Yealink/Unify Square Device
- Management Platform
- Wall mountable

Technical Specifications

Specifications	Introduction
Audio Features	HD voice: HD handset, HD speaker
	Hearing aid compatible (HAC) handset, magnet handset
	Yealink Noise Proof Technology
	 Audio codec: SILK, G.722, G.722.1, G.722.1C, G.711 (A/μ), G.723, G.726, G.729AB, iLBC
	Full-duplex hands-free speakerphone with AEC
	• VAD, CNG, AEC, PLC, AJB, AGC
	Incoming/Outgoing P2P call
	Cloud PSTN call
	Call controls
	Call hold/Call mute/Call transfer/Call forward
	Visual voicemail
	Synchronized call logs
	Exchange calendar integration
	Meeting call controls
	Mute/unmute, hold/resume
Phone Features	• Hang up
	Add/remove participant
	Sign in with user credentials
	Sign in via website
	Phone lock/unlock
	Emergency calls
	Hot desking
	• Accessibility
	Power saving
	Common Area Phone (CAP)

Yealink

Display and Indicator	 Color screen with backlight: 2.4 inch (320 x 240) non-touch Screen Dark theme Multi-language user interface Power LED for call and message waiting indication Presence status control: available, busy, DND, be right back, off work, appear away Voice Mail button Time display
Interface	 Dual-port 10/100M Ethernet, Supports PoE Power over Ethernet (IEEE 802.3af), class 3 1 x USB Type-A port 1 x Security lock port 1 x RJ9 (4P4C) handset port 1 x RJ9 (4P4C) headset port
Management	 Configuration: Browser/Phone/Auto Provisioning and Device Management Platform Provisioning priority management Auto Provisioning via Activation Code Yealink Redirection and Provisioning Service (RPS) QoE (Monitoring Reports) Reset to factory, reboot Package tracing export, system log Screenshot via URL Supports Microsoft Device Management Platform Supports Yealink Device Management Platform Supports Unify Square Device Management Platform Simple Certificate Enrollment Protocol (SCEP)
Network and Security	 IPv4/IPv6 IP Assignment: Static/DHCP Proxy mode HTTP/HTTPS web server Time and date synchronization using SNTP Transport Layer Security (TLS) HTTPS certificate manager IEEE802.1X AES encryption for configuration file

Yealink

Other Physical Features	Color: Classic Grey
	• External Yealink AC adapter (optional): AC 100-240 V input and DC 5 V/2 A output
	• USB output currency: 5 V/500 mA
	 Power consumption (PSU): 1.5-4.5 W
	• Power consumption (PoE): 2.3-6.0 W
	• Dimension (W \times D \times H \times T): 212 \times 186 \times 146 \times 42 mm
	• Operating humidity: 10-95%
	 Operating temperature: -10-50°C (+14-122°F)
Package Features	Package content:
	Yealink MP52 IP phone
	Handset with handset cord
	Ethernet Cable (2m CAT5E FTP Cable)
	• Stand
	Quick Start Guide
	Power Adapter (Optional)
	• Qty/CTN: 10 PCS
	• N.W/CTN: 10.7 kg
	• G.W/CTN: 11.6 kg
	• Giftbox size: $238 \times 210 \times 103$ mm
	• Carton Meas: 535 \times 443 \times 250 mm
Compliance	CE DE FC DE